



SAFETY DATA SHEET
OVEN CLEANER RTU

Page 1
Issued: 02/10/2002
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: OVEN CLEANER RTU
Use / description of product: Irritant.
Company name: Greyland Ltd
Greg Street
South Reddish
Stockport
Cheshire
SK5 7BX
United Kingdom
Tel: +44 (0) 161 476 3607
Fax: +44 (0) 161 477 1870
Emergency tel: +44 (0) 161 476 3607

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients: DISODIUM METASILICATE 1-10%
CAS: 6834-92-0
EINECS: 229-912-9
[C] R34; [Xi] R37

- 2-(2-BUTOXYETHOXY)ETHANOL 1-10%
CAS: 112-34-5
EINECS: 203-961-6
[Xi] R36
- 2-BUTOXYETHANOL 1-10%
CAS: 111-76-2
EINECS: 203-905-0
[Xn] R20/21/22; [Xi] R36/38
- 01824700 1-10%
CAS: 68439-45-2
[Xn] R22; [Xi] R41
- 02845000 1-10%
CAS: 1300-72-7
[Xi] R36

3. HAZARDS IDENTIFICATION

Main hazards: Irritating to eyes and skin.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

[cont...]

SAFETY DATA SHEET

OVEN CLEANER RTU

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients: 2-BUTOXYETHANOL
TWA (8 hr exposure limit): 25 ppm STEL (15 min exposure limit): 50 ppm (OES)

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid
Colour: Yellow-green
Odour: Characteristic odour
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Soluble
Also soluble in: Most organic solvents.
Viscosity: Non-viscous
pH: 12.5

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Ingredients: 2-BUTOXYETHANOL
ORL RAT LD50 470 mg/kg

- 01824700
ORL RAT LD50 >200<2000 mg/kg
- 02845000
ORL RAT LD50 >7000 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.
Persistence and degradability: Biodegradable.
Bioaccumulative potential: No bioaccumulation potential.
Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1760	ADR Class: 8
Packing group: III	Classification code: C9
Hazard ID no: 80	Labelling: 8
Shipping name: CORROSIVE LIQUID, N.O.S.	
Technical name(s): (DISODIUM METASILICATE)	

SAFETY DATA SHEET

OVEN CLEANER RTU

IMDG / IMO

UN no: 1760	Class: 8
Packing group: III	EmS: 8-15
Marine pollutant: .	Labelling: 8

IATA / ICAO

UN no: 1760	Class: 8
Packing group: III	Packing instructions: 818(P&CA); 820(PAO)
Labelling: 8	

15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R36/38: Irritating to eyes and skin.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R34: Causes burns.
 R37: Irritating to respiratory system.
 R36: Irritating to eyes.
 R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
 R36/38: Irritating to eyes and skin.
 R22: Harmful if swallowed.
 R41: Risk of serious damage to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.